

ULTRAVIEW 5

SPECIFICATIONS

	Single Pane	Double Pane
Visible Light Transmission	6%	6%
Visible Light Reflectance (Ext)	56%	55%
Visible Light Reflectance (Int)	15%	15%
Shading Coefficient (SC)	0.23	0.34
Solar Heat Gain Coefficient	0.20	0.29
Solar Absorption	37%	32%
Total Solar Energy Rejected	80%	71%
U-Value	0.96	0.46
UV Rejection	>99%	>99%

BENEFITS:

- Residential limited lifetime Warranty
- Extended Commercial Warranty
- Improved Energy Savings and Comfort
- Durable Scratch-Resistant Coating for Long Life
- Clarity and Elegance
- Blocks over 99% of UV Rays
- SPF>200

ProgramEdge.com
888.660.3456
5821 West Sam Houston Pkwy N
Houston, TX 77041

ULTRAVIEW 5

**ULTRAVIEW
15**

**ULTRAVIEW
15**

EDGE SOLAR FILM BENEFITS:

- Residential Lifetime Warranty
- Extended Commercial Warranty
- Improved Energy Savings and Comfort
- Durable Scratch-Resistant Coating for Long Life
- Clarity and Elegance
- Blocks over 99% of UV Rays
- SPF>200

SPECIFICATIONS

	Single Pane	Double Pane
Visible Light Transmission	14%	13%
Visible Light Reflectance (Ext)	48%	49%
Visible Light Reflectance (Int)	21%	21%
Shading Coefficient (SC)	0.29	0.40
Solar Heat Gain Coefficient (SHGC)	0.25	0.35
Solar Absorption	39%	33%
Total Solar Energy Rejected (TSER)	75%	65%
U-Value	0.96	0.46
UV Rejection	>99%	>99%

**ULTRAVIEW
25**

**ULTRAVIEW
25**

EDGE SOLAR FILM BENEFITS:

- Residential Lifetime Warranty
- Extended Commercial Warranty
- Improved Energy Savings and Comfort
- Durable Scratch-Resistant Coating for Long Life
- Clarity and Elegance
- Blocks over 99% of UV Rays
- SPF>200

SPECIFICATIONS

	Single Pane	Double Pane
Visible Light Transmission	27%	25%
Visible Light Reflectance (Ext)	27%	31%
Visible Light Reflectance (Int)	14%	15%
Shading Coefficient (SC)	0.47	0.56
Solar Heat Gain Coefficient (SHGC)	0.40	0.48
Solar Absorption	44%	37%
Total Solar Energy Rejected (TSER)	60%	52%
U-Value	0.99	0.47
UV Rejection	>99%	>99%

**ULTRAVIEW
35**

**ULTRAVIEW
35**

EDGE SOLAR FILM BENEFITS:

- Residential Lifetime Warranty
- Extended Commercial Warranty
- Improved Energy Savings and Comfort
- Durable Scratch-Resistant Coating for Long Life
- Clarity and Elegance
- Blocks over 99% of UV Rays
- SPF>200

SPECIFICATIONS

	Single Pane	Double Pane
Visible Light Transmission	38%	34%
Visible Light Reflectance (Ext)	13%	19%
Visible Light Reflectance (Int)	8%	10%
Shading Coefficient (SC)	0.63	0.69
Solar Heat Gain Coefficient (SHGC)	0.55	0.60
Solar Absorption	44%	37%
Total Solar Energy Rejected (TSER)	45%	40%
U-Value	1.02	0.48
UV Rejection	>99%	>99%