



PremiumShield

THE BEST PROTECTION YOU'LL NEVER SEE



BLACK

ULTRA SMOOTH, HIGH GLOSS PAINT PROTECTION



BLACK

OPAQUE & HIGH GLOSS ACCENTS

HIGH PERFORMANCE SURFACE PROTECTION

PremiumShield® BLACK is the answer to the demand for a super high-gloss black surface that must also be scratchproof, dirt-repellent and stone-chip resistant.

This high-gloss polyurethane film is perfect for application on accent areas such as car roofs, mirrors, hoods, and spoilers, as well as full body vehicle colour changes.

The 'custom' look combined with self-healing protective properties, makes this film a MUST HAVE for any modern enthusiast.




- High Gloss Urethane Film
- Reliable protection
- Perfect for accents
- Self-healing top coat
- 5 Year Warranty



Characteristics

PremiumShield® BLACK is a high-gloss black 0.16 mm thick aliphatic polyurethane film (PU) with a 0.04 mm thin, pressure sensitive acrylic adhesive layer (PSA).

The film is specially designed to add decorative accents to different areas, as well as protecting paints, gel coatings or other sensitive surfaces, thus improving the service life.



| Technical Information | |
|---|----------------------|
| Type: | Polyurethane |
| Colour and surface: | High Gloss Black |
| Thickness: | 150 microns (6 mil) |
| Elongation - percent (ASTM D882): | 400% |
| Peel (PSTC-101) 3D/RT/SS: | 705Nm/25mm |
| Shear (PSTC-101) 1hr Dwell/SS: | Avg 257 mins/4:28 hr |
| Gravelometer (SAEJ4000): | Pass (no ruptures) |
| Outdoor Weathering - 24 months: Arizona 45° South Exposure (Range 35°-105°F) | Pass (no changes) |
| Chemical resistance: Isopropanol/water 1:1 Carburettor cleaner (brushing test) | Pass (no effect) |

After Care Instructions

NOTE: The film should be left a minimum of 48 hours to allow the pressure sensitive adhesive time to fully cure and all of the moisture to evaporate completely. After the curing process has passed, follow the simple maintenance instructions below.

Cleaning

Always remove contaminants (insect debris, bird droppings, etc.) immediately. If left on the film for a longer period of time, stains can form, just as the acids contained would eventually damage the paint.

We recommend using **PremiumShield Insect Remover**, which has been specially designed to gently and efficiently remove insect debris, and bird lime.

Washing & rinsing

We suggest using a twin bucket method, along with a lambswool wash mitt for a gentler clean. If you choose to use a pressure washer, ensure the lance is at least 3 feet away from the surface of the film, avoiding any edges to prevent lifting.

We recommend using **PremiumShield Shampoo**, which provides a pH neutral construction for a thorough wash.

Drying

Use a normal moisture absorbant cloth to dry the film the same as you would the rest of the vehicle.

Once dry use a clean microfibre cloth to polish with **PremiumShield Premium Seal**.

Scientifically designed to enhance the film, Premium Seal provides an additional level of protection to the films' surface. This should be reapplied every 3-6 months for maximum benefit.

For regular maintenance after washing **PremiumShield Spray and Shine** quick detailer spray may be used to maintain the slickness on the surface of the film.

If you wish to maintain your vehicle using alternative products, we recommend avoiding polishes that contain abrasives, petroleum, solvents or that are resin based as this will damage the PPF, always use synthetic based waxes.

Cleaning edges

Over time wax and dust can stick to the film edges. For cleaning, use a regular cotton swab dipped in 70% isopropynol alcohol (IPA or rubbing alcohol) and wipe it AWAY from the edge, NOT towards the edge to remove any residue.

Things to avoid...

Do not use solvent-based cleaners, insect removers, degreasers or other abrasive materials. Polishing equipment may be used, but at low speed and with minimal force.

We recommend that you test on a small area out of sight before proceeding fully.

PremiumShield® is the market leader in paint protection for vehicles. **PremiumShield®** has been tested worldwide and the results prove time and again that our products are among the clearest and strongest paint protection films on the market. We are so confident that **PremiumShield® ELITE-SH** has a LIFETIME WARRANTY*.



PremiumShield

WWW.PREMIUMSHIELD.COM

All statements, technical data sheets and recommendations published by **PremiumShield®** are based on test results which have been relied upon to be reliable and to respect the tolerances of the equipment used to determine these specific values. We cannot guarantee the precision and completeness thereof and cannot accept any liability in this respect. The reseller and supplier are not liable for injury, loss of profit or damage (s) as a result of the use by or the unsuitability of this product for the buyer. Moreover, neither the seller, nor the producer, nor the supplier are liable for costs incurred during the processing of the product. Before using the product, the user must test its suitability for the intended application. The user is responsible for all possible risks and liabilities in any form as a result of using the product. Any statements or recommendations to the contrary are void or invalid, unless they are published in the technical information or in an agreement signed by an authorized representative of the sales organization, the supplier or the manufacturer.